



CUT LEVEL 5 NITRILE DIPPED GLOVES

MORE DURABLE. BETTER PROTECTION.



CUT LEVEL 5

ANSI/ISEA 105



EN388 STANDARDS

Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTSWIPE™ Touch
Screen Compatible
Fingertips & Palms



High Dexterity
Fingertips

Sandy Nitrile Grip

Light &
Breathable Back

Color-Coded Bands
Easy cut level
identification

SPECIFICATIONS		RECOMMENDED APPLICATIONS	CARE INSTRUCTIONS
Gauge	13	<ul style="list-style-type: none"> ■ Duct Work ■ Cutting ■ High Dexterity Applications ■ Oily & Wet Conditions ■ Abrasive / Sharp Materials ■ Glass & Metal Handling 	Machine wash warm water (105°F), mild detergent, no bleach. Line dry.
Liner Material	Nylon and HPPE Blend Knit		
Dip Material	Sandy Nitrile		
Cuff Style	Elasticated Knit		

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8650	48-73-8650E
M	48-73-8651	48-73-8651E
L	48-73-8652	48-73-8652E
XL	48-73-8653	48-73-8653E
XXL	48-73-8654	48-73-8654E

SEE MORE PPE



or visit <https://qr.mke.tl/2d235>

Milwaukee[®]

The Milwaukee logo is rendered in a white, stylized, gothic-style font. The word "Milwaukee" is slanted upwards to the right. Below the text is a white lightning bolt graphic that also slants upwards to the right, matching the angle of the text. A small registered trademark symbol (®) is located at the top right of the word.